APPROVED BY DRAFTSMAN | O.G. FIG. | CLASS 370 | SUBCLASS 235



Figure 1

09/752,870

APPROVED BY DRAFTSMAN
CLASS 370
O.G. FIG.
SUBCLASS 235



Figure 2

APPROVED BY DRAFTSMAN | O.G. FIG. | CLASS | SUBCLASS



Figure 3

APPROVED BY DRAFTSMAN | O.G. FIG. | CLASS | SUBCLASS



Figure 4

APPROVED
BY
DRAFTSMAN
CLASS
SUBCLASS
C.G. FIG.



Figure 5

APPROVED
BY
DRAFTSMAN
CLASS
SUBCLASS



Figure 6

APPROVED BY DRAFTSMAN | O.G. FIG. | CLASS | SUBCLASS

AvgBufCnt or BufCnt	PkCntThr	Alpha
0 % - 6.25 %	0	0.001953125
6.25 % - 12.5 %	0	0.001953125
12.5 % - 18.75 %	0	0.001953125
18.75 % - 25 %	0	0.001953125
25 % - 31.25 %	80	0.001953125
31.25 % - 37.5 %	70	0.001953125
37.5 % - 43.75 %	60	0.001953125
43.75 % - 50 %	50	0.001953125
50 % - 56.25 %	40	0.00390625
56.25 % - 62.5 %	30	0.00390625
62.5 % - 68.75 %	20	0.00390625
68.75 % - 75 %	10	0.00390625
75 % - 81.25 %	1	0.0078125
81.25 % - 87.5 %	1	0.0078125
87.5 % - 93.75 %	1	0.0078125
93.75 % - 100 %	1	0.0078125
CongThr :	25%	
ClCntThr :	210 cells	
Switch Buffer Size (per port) :	8192 cells	

Figure 7

66E22T 28204460

APPROVED
BY
DRAFTSMAN
CLASS
SUBCLASS



Figure 8

66E22T" 28204n60

APPROVED
O.G. FIG.
BY
CLASS
SUBCLASS
DRAFTSMAN



Figure 9

09470787 "J22399
66E22T"



Figure 10

APPROVED
O.G. FIG.
BY
DRAFTSMAN
CLASS
SUBCLASS



Figure 11